

## N THE UNITED STATES PATENT AND TRADEMARK OFFICE

INVENTOR(S):

Masahiro IWADARE

Title:

FAST CALCULATION APPARATUS FOR CARRYING OUT A FORWARD AND AN INVERSE TRANSFORM

**Application Number:** 

10/642,968

Filing Date

08/19/2003

Examiner:

C. Ngo

Art Unit:

2124

## SUPPLEMENTAL AMENDMENT

**Assistant Commissioner for Patents** 

P.O. Box 1450

Alexandria, VA 22313-1450

Sir:

Please amend the reissue application claims as follows:

## IN THE CLAIMS:

Please amend the claims as follows:

44. (New) An apparatus for carrying out an inverse transform comprising: an input signal y(m,k) having M samples, M being an integer;

transform carrying out means for carrying out a linear inverse transform on said input signal y(m,k) and for outputting an inverse transformed signal xt(m,n) representative of a result of said linear inverse transform, said linear inverse transform xt(m,n) being determined using the sum:

$$\frac{M-1}{\sum y(m,k) \cos[2\pi(n+n0)(k+1/2)/N]}$$
  
k = 0

01/13/2005 HLE333 00000015 10642968

01 FC:1201 02 FC:1202 200.00 OP 150.00 OP where m represents a block number, n represents a sample number, N represents a block length and k is an integer between 0 and M-1;

a multiplier connected to said transform carrying out means, said multiplier multiplying a predetermined inverse transform window function and said inverse transformed signal xt(m,n) to produce a product signal having N samples, N being an integer different from M;

wherein said transform carrying out means comprises:

a first processing device which receives said input signal y(m,k)and outputs a processed signal, said processed signal comprising a product signal formed by multiplying said input signal y(m,k) by a predetermined factor;

internal transform carrying out means connected to said first processing device for carrying out an inverse fast Fourier transform on said processed signal and for outputting as a result of said inverse fast Fourier transform an internal signal; and

a second processing device connected to said internal transform carrying out means to receive said internal signal and output as a result of processing said internal signal said inverse transformed signal.

- 45. (New) The apparatus as claimed in claim 44, wherein M is smaller than N.
- 46. (New) The apparatus as claimed in claim 44, wherein M is equal to N/2.